

Powder Compacting Press

S - 6 S - 15 S - 20

SPECIFICATIONS				
		S-6	S-15	S-20
Max. Pressing Capacity	kN	60	150	200
Ejection Capacity	kN	60	150	200
Depth of Fill	mm	60	100	100
Lower Pressing Stroke	mm	15	25	35
Ejection Stroke	mm	45	75	65
Upper Ram Stroke	mm	110	130	150
Upper Punch Adjustment	mm	25	60	60
Die Ejection Level Adjustment	mm	35	75	65
Lower Ram Pressing Capacity	kN	30	70	100
Max. Compact Diameter	mm	45	75	75
Feeder Stroke	mm	115	130	130
Pressure Indicator		Hydraulic		
Motor	kw	2.2	3.7	3.7
Stroke Per Minute at 50Hz	s/m	10-40		
Speed Variator		BeltType (1:4)		
Clutch & Brake		Air Clutch/Spring Return Brake		
Lubrication		Centralized Grease Pump		
Air Pressure Required	Mpa	0.5-0.7		
Press Net Weight (Without Dieset)	kg	900	1300	2300

Option

- * Digital Pressure Gauge.
- * Upper Punch Hold Down Device. (S-6, S-15)
- * Float Core Device.(S-20)
- * Under Fill / Over Fill Device. (S-20)
- * Die Set Support.
- * Table Lifter, etc.