

Powder Compacting Press

T-HS-10N T-HS-20N

SPECIFICATIONS			
		T-HS-10N	T-HS-20N
Max. Pressing Capacity	tf	10	20
Ejection Capacity	tf	3	5
Depth of Fill (Die)	mm	15	20
Depth of Fill (Float Punch)	mm	15	20
Ejection Stroke	mm	15	20
Upper Ram Stroke	mm	60	70
Upper Punch Hold-Down Capacity	kg	50	
Upper Punch Hold-Down Stroke	mm	18	15
Upper Punch Adjustment	mm	30	
Die Ejection Level Adjustment	mm	5	
Float Punch Ejection Level Adjustment	mm	5	
Float Punch Stop Capacity	tf	10	20
Float Punch Stopper Adjustment	mm	10	
Max. Compact Size	mm	60(w) * 20(L)	40(w) * 40(w)
Feeder Stroke	mm	60	70
Motor	kw	2.2	3.7
Stroke Per Minute at 50Hz	s/m	25-100	20-80
Speed Variator		Belt Type (1:4)	
Clutch & Brake		Air Clutch/Spring Return Brake	
Lubrication		Automatic Oilbath Pressurized System	
Air Pressure Required	kg/cm ²	5-7	
Press Net Weight	kg	1650	3200

Option

*Pressing Force Indicator.

*Photoelectric Safety Device.

*Automatic Filling Height Control Device, etc.